

# USCG ACCEPTED LIFEBOAT/RESCUE BOAT ENGINES

## Model Year 2014 Accepted SOLAS Lifeboat/Rescue Boat Inboard Diesel Engines meeting US EPA Tier II or higher emission requirements

*Gauge packages for inboard engines on USCG approved lifeboats/rescue boats must include: coolant temperature for a liquid cooled engine; oil pressure for an engine with an oil pump; tachometer for an engine not provided with overspeed protection; state of charge or rate of charge for each rechargeable engine starting power source.*

**Steyr Motors GmbH, Im Stadtgut B1, A-4407 Steyr, Austria**  
**Tel.: +43 (0)7252/222, Fax: +43 (0)7252/222-29, office@steyr-motors.com**

All engines listed below are 4 stroke, turbocharged and raw/fresh water-cooled via heat exchanger. SOLAS kit required from manufacturer.

### Inboard engine models:

SE114E33, 80 kW@3300 rpm, 4 cylinder  
SE144E38, 100 kW@3800 rpm, 4 cylinder  
SE164E40, 117 kW@4000 rpm, 4 cylinder  
SE174S40, 125 kW@4000 rpm, 4 cylinder  
SE126E25, 88 kW@2500 rpm, 6 cylinder  
SE156E26, 110 kW@2600 rpm, 6 cylinder  
SE196E35, 140 kW@3500 rpm, 6 cylinder  
SE236E40, 170 kW@4000 rpm, 6 cylinder  
SE236S36, 170 kW@3600 rpm, 6 cylinder  
SE266E40, 190 kW@4000 rpm, 6 cylinder  
SE266S36, 190 kW@3600 rpm, 6 cylinder  
SE286E40, 205 kW@4000 rpm, 6 cylinder  
SE306J38, 215 kW@3800 rpm, 6 cylinder

STEYR M14TCAM Model 114K33, 81 kW@3300 rpm, 4 cylinder  
STEYR M14TCAM Model 144M38, 106 kW@3800 rpm, 4 cylinder  
STEYR M14TCAM Model 144V38, 106 kW@3800 rpm, 4 cylinder  
STEYR M14TCAM Model 164M40, 120 kW@4000 rpm, 4 cylinder  
STEYR M14TCAM Model 174V40, 125 kW@4000 rpm, 4 cylinder