

SELECTION-TABLE VETUS EQUIPMENT FOR YANMAR ENGINE RANGE 150-370HP

	BY3-150	BY3-180	BY3-220	BY3-260	6LPA-STP2	8LV320	8LV370
Power/max rpm	150 hp	180 hp	220 hp	260 hp	315hp	320 hp	370hp
Gearbox ratio	1,53:1 2,62:1	1,53:1 2,62:1	1,67:1 2,43:1	1,67:1 2,43:1	2,04:1 2,52:1	1,67:1 2,43:1	1,93:1 2,78:1
VETUS waterlubricated sterngear systems							
* minimum shaftdiam., duplex 1-4462	35 40	35 40	40 45	40 45	45 50	45 50	45 50
VETUS manganese bronze propellers for displacement boats							
* 3 or 4-blade	on request						
VETUS flexible couplings:							
* Bullflex type:	08 12	08 12	12 16	12 16	16 32	16 32	32 32
* Adaptor flange	CT50009(KMH40/41A+50/51A)						
VETUS water strainers							
* hose connection in diam.(mm)	38	38	38	38	45	38	38
* water strainer, type FTR:	FTR525	FTR525	FTR525	FTR525	FTR525	FTR525	FTR525
VETUS water separator/fuel filter							
* hose connection supply/return in mm	10-12	10-12	10-12	10-12	9-9	10-10	10-10
* water separator/fuel filter, type:	340VTE(P)B	340VTE(P)B	340VTE(P)B	340VTE(P)B	340VTE(P)B	340VTE(P)B	340VTE(P)B
VETUS water injected exhaust systems							
* exhaust hose, diam.(mm)	102	102	102	102	100	102	102
* waterlock, type:	MF or MGP	MF or MGP	MF or MGP	MF or MGP	MF or MGP	MF or MGP	MF or MGP
* muffler, type:	MP100	MP100	MP100	MP100	MP100	MP100	MP100
* goose neck, type:	LT102	LT102	LT102	LT102	LT102	LT102	LT102
* exhaust transom connection type TRC..R, PV or SV	TC/TRC..SV	TC/TRC..SV	TC/TRC..SV	TC/TRC..SV	TC/TRC..SV	TC/TRC..SV	TC/TRC..SV
* breather, type ASD or AIRVENT	V or H	V or H	V or H	V or H	V or H	V or H	V or H
VETUS maintenance free batteries							
* voltage	12	12	12	12	12	12	12
* starting battery, min. Ah.	VESMF125	VESMF125	VESMF125	VESMF125	VESMF125	VESMF125	VESMF125
* light battery, Ah.	to be selected						
VETUS louvred air suction vents							
* per engine, type:	2 x ASV080A	2 x ASV090A	2 x ASV050A + 2 x ASV060A	2 x ASV060A + 2 x ASV070A	4 x ASV080A	4 x ASV080A	2 x ASV090A + 2 x ASV100A