

SELECTION-TABLE VETUS EQUIPMENT FOR YANMAR ENGINES RANGE 29-110HP

	3YM30AE		4JH 45CR		4JH 57CR		4JH 80CR		4JH 110CR	
Power/max rpm	29hp/3200		45hp/3000		57hp/3000		80hp/3200		110hp/3200	
Gearbox ratio	2,21:1	2,62:1	2:1	2.5:1	2:1	2,47:1	2:1	2.63:1	1.97:1	2.8:1
VETUS waterlubricated sterngear systems										
* minimum shaftdiam., duplex 1-4462	25	25	25	30	30	30	30	35	35	40
VETUS manganese bronze propellers for displacement boats										
* 3-blade, P3B, diameter in inches	on request									
* 4-blade, P4E, diameter in inches	on request									
VETUS flexible couplings:										
* Bullflex type:	02	04	04	04	04	08	08	08	08	12
* Uniflex type:	13	13	13	13	16	16	16	16	16	16
Adaptor flange	FLANGE1(KM2P, KM3P), FLANGE3(KM4A, KMH4A), CT50082(ZF25(A)), CT 50009(Bullflex 8/16 icm TM345)									
VETUS water strainers										
* hose connection in diam.(mm)	19		26		26		26		26	
* water strainer, type FTR470 or FTR330:	330 or 470/19		330 or 470/25		330 or 470/25		330 or 470/25		330 or 470/25	
* water strainer kit, type:	WKIT33019		WKIT33025		WKIT33025		WKIT33025		WKIT33025	
VETUS water separator/fuel filter										
* hose connection supply/return in mm	8-8		8-8		8-8		8-8		8-8	
* water separator/fuel filter, type:	330VTEB or 75330VTEB		340VTEB or 75340VTEB		340VTEB or 75340VTEB		340VTEB or 75340VTEB		340VTEB or 75340VTEB	
VETUS water injected exhaust systems										
* exhaust hose, diam.(mm)	51		76		76		76		76	
* waterlock, type:	NLP(3)50/LP50		NLP(3)75/LP75		NLP(3)75/LP75		NLP(3)75/LP75		NLP75/LP75	
* combi waterlock/muffler, type:	NLPH50		NLPH75		NLPH75		NLPH75		NLPH75	
* muffler, type:	MP50		MP75		MP75		MP75		MP75	
* goose neck, type:	LT50		LT7575		LT7575		LT7575		LT7575	
* combi muffler/goose neck, type:	NLPG50		NLPG75		NLPG75		NLPG75		NLPG75	
* exhaust transom connection type TRC..R, PV or SV	50R/PV or SV		TRC7590R/75P(S)V		TRC7590R/75P(S)V		TRC7590R/75P(S)V		TRC7590R/75P(S)V	
* breather, type ASD or AIRVENT	V or H		V or H		V or H		V or H		V or H	
VETUS engine remote controls										
* to be selected	SICO, SICOG, SISCO, SISCOG, RCTOPB, RCTOPBG, RCTOPS, RCTOPSG, RCTOPTS, RCTOPTSG, AFSTTOP, AFSTTOPT									
VETUS maintenance free batteries										
* voltage	12		12		12		12		12	
* starting battery, min. Ah.	VESMF85		VESMF85		VESMF85		VESMF85		VESMF85	
* light battery, Ah.	to be selected									
VETUS louvred air suction vents										
* per engine, type:	2 x ASV020		2 x ASV025		2 x ASV030		2 x ASV040		2 x ASV060	