



## SELECTION-TABLE VETUS EQUIPMENT FOR YANMAR ENGINES RANGE 9-125HP

	1GM10		2YM15		3YM20		3YM30		3JH 5-E		4JH 5-E		4JH 4-TE		4JH 4HTE		4JH 3-DTE	
Power/max rpm	9.1hp/3600		14hp/3600		21hp/3600		29hp/3600		39hp/3000		54hp/3000		75hp/3200		110hp/3200		125hp/3800	
Gearbox ratio	2,21:1	2,62:1	2,21:1	2,62:1	2,21:1	2,62:1	2,21:1	2,62:1	2:1	2.5:1	2:1	2,47:1	2:1	2,63:1	1,97:1	2,8:1	1,97:1	2,8:1
<b>VETUS waterlubricated sterngear systems</b>																		
* minimum shaftdiam., duplex 1-4462	25	25	25	25	25	25	25	25	25	30	30	30	30	35	35	40	35	40
<b>VETUS manganese bronze propellers for displacement boats</b>																		
* 3-blade, P3B, diameter in inches	on request																	
* 4-blade, P4E, diameter in inches	on request																	
<b>VETUS flexible couplings:</b>																		
* Bullflex type:	n.a.		n.a.		02	02	02	04	04	04	04	08	08	08	08	12	08	12
* Uniflex type:	13	13	13	13	13	13	13	13	13	13	13	16	16	16	16	nvt	16	nvt
Adaptor flange	FLANGE1(KM2P, KM3P), FLANGE3(KM4A, KMH4A), CT50082(ZF25(A)), CT 50009(Bullflex 8/16 icm TM345)																	
<b>VETUS water strainers</b>																		
* hose connection in diam.(mm)	14		19		19		19		26		26		26		26		26	
* water strainer, type FTR470 or FTR330:	330 or 470/13		330 or 470/19		330 or 470/19		330 or 470/19		330 or 470/25		330 or 470/25		330 or 470/25		330 or 470/25		330 or 470/25	
* water strainer kit, type:	WKIT33013		WKIT33019		WKIT33019		WKIT33019		WKIT33025		WKIT33025		WKIT33025		WKIT33025		WKIT33025	
<b>VETUS water separator/fuel filter</b>																		
* hose connection supply/return in mm	8.3-8.3		8-8		8-8		8-8		8-8		8-8		8-8		8-8		8-8	
* water separator/fuel filter, type:	330VTEB or 75330VTEB		330VTEB or 75330VTEB		330VTEB or 75330VTEB		330VTEB or 75330VTEB		330VTEB or 75330VTEB		330VTEB or 75330VTEB		330VTEB or 75330VTEB		330VTEB or 75330VTEB		330VTEB or 75330VTEB	
<b>VETUS water injected exhaust systems</b>																		
* exhaust hose, diam.(mm)	45		51		51		51		76		76		76		76		76	
* waterlock, type:	NLP(3)45/LP45		NLP(3)50/LP50		NLP(3)50/LP50		NLP(3)50/LP50		NLP(3)75/LP75		NLP(3)75/LP75		NLP(3)75/LP75		NLP75/LP75		NLP75/LP75	
* combi waterlock/muffler, type:	NLPH45		NLPH50		NLPH50		NLPH50		NLPH75		NLPH75		NLPH75		NLPH75		NLPH75	
* muffler, type:	MP45		MP50		MP50		MP50		MP75		MP75		MP75		MP75		MP75	
* goose neck, type:	LT45		LT50		LT50		LT50		LT7575		LT7575		LT7575		LT7575		LT7575	
* combi muffler/goose neck, type:	NLPG45		NLPG50		NLPG50		NLPG50		NLPG75		NLPG75		NLPG75		NLPG75		NLPG75	
* exhaust transom connection type TRC..R, PV or SV	45R/PV of SV		50R/PV of SV		50R/PV of SV		50R/PV of SV		TRC7590R/75P(S)IV		TRC7590R/75P(S)IV		TRC7590R/75P(S)IV		TRC7590R/75P(S)IV		TRC7590R/75P(S)IV	
* breather, type ASD or AIRVENT	V or H		V or H		V or H		V or H		V or H		V or H		V or H		V or H		V or H	
<b>VETUS engine remote controls</b>																		
* to be selected	SICO, SICOG, SISCO, SISCOG, RCTOPB, RCTOPBG, RCTOPS, RCTOPSG, RCTOPTS, RCTOPTSG, AFSTTOP, AFSTTOPT																	
<b>VETUS maintenance free batteries</b>																		
* voltage	12		12		12		12		12		12		12		12		12	
* starting battery, min. Ah.	VESMF70		VESMF85		VESMF85		VESMF85		VESMF85		VESMF85		VESMF85		VESMF85		VESMF85	
* light battery, Ah.	to be selected		to be selected		to be selected		to be selected		to be selected		to be selected		to be selected		to be selected		to be selected	
<b>VETUS louvred air suction vents</b>																		
* per engine, type:	1 x ASV020		1 x ASV020		2 x ASV020		2 x ASV020		2 x ASV020		2 x ASV030		2 x ASV040		2 x ASV060		2 x ASV070	